

Concrete Processor (GCP)

FEATURES

- 1 One-piece bolt-on tooth bed and bottom wear pad protect parent material, are quick and easy to replace, and minimize build-up and hard-surfacing
- 2 Bolt-on rebar cutting blades and weld-in blade pockets are easy to replace and reduce maintenance
- 3 Large jaw opening readily pulverizes thick concrete
- 4 Unique bolt-on wear parts quickly separate rebar from concrete
- 5 Heavy-duty pivot design with recessed end caps provides structural strength and long-term durability
- 6 Proprietary regeneration valve improves cycle time by up to 33% compared to standard hydraulic systems

APPLICATIONS

- Concrete Recycling
- Demolition



Model	Weight*	Jaw Opening	Jaw Depth	Jaw Width	Reach**	Minimum Excavator Wt.
	(lbs.)	(ins.)	(ins.)	(ins.)	(ft. ins.)	Stick Mount (lbs.)
GCP 410	4,650	34	29	20	6' 9"	45,000
GCP 410R	6,650	34	29	20	7' 9"	55,000
GCP 510	8,000	41	34.5	28	9' 4"	70,000
GCP 510R	9,700	41	34.5	28	10' 8"	90,000
GCP 610	10,950	49	40	30	10' 7"	90,000
GCP 610R	11,900	49	40	30	11' 9"	100,000

*Weight includes mounting bracket to attach to excavator.

**Distance is measured from the attachment mounting pivot (boom or stick) forward.

Genesis Concrete Processors are covered by a 12-month, 1,500-hour (whichever occurs first) warranty.

Genesis reserves the right to continually make product improvements designed to positively enhance performance.

Patents: genesisattachments.com/products/patents