

Rebar Processor (GRP)



FEATURES

- ① Extra large, heavy-duty pivot group provides durability for increased processing
- ② Open lower jaw design eliminates jamming
- ③ Replaceable piercing blades work with full-length lower blades to sort/separate rebar bundles
- ④ Bolt-on upper jaw side plate provides a replaceable wear surface and protects the jaw
- ⑤ Weld-on top guard minimizes build-up and maintenance
- ⑥ Dual AutoGuides maintain proper jaw alignment and extend bearing life
- ⑦ Maxx-NiFe® blades standard



**SHEAR
JAW ARMOR®
COMPATIBLE**

APPLICATION

Rebar Processing

Model	Weight*	Jaw Opening	Jaw Depth	Reach**	Minimum Excavator Wt.	
					Boom Mount (lbs.)	Stick Mount (lbs.)
GRP 480	11,900 (lbs.)	24 (ins.)	26 (ins.)	10' 1" (ft. ins.)	48,000	90,000

*Weight includes mounting bracket to attach to excavator.

**Distance is measured from the attachment mounting pivot (boom or stick) forward.

The GRP is covered by a 12-month, 1,500-hour (whichever occurs first) warranty.

Genesis reserves the right to continually make product improvements designed to positively enhance performance.

Patents: genesisattachments.com/products/patents