Versi Pro 15_ (GVP 15)





FEATURES

- Patented pivot system provides a power curve to match each jaw set's primary application
- 2 360° rotation comes standard with every Versi Pro
- Optimize the second state of the second sta improves cycle time by up to 33% compared to standard hydraulic systems
- Each jaw's pivot group stays intact, allowing the use of a press-fit pin design for a stronger, more durable product and making jaw changeouts safe, easy and fast
- 5 Jaw change-outs in 10 minutes with the coupler-style connection system

APPLICATIONS

Shear Jaws

- Scrap Processing
- Demolition - Rebar
- Wire
- Tires
- Many types of non-ferrous

Shear Jaws



Four-way indexable guide blades, razor blade and primary blades provide four useable cutting edges

Exclusive dual guide blade system accommodates heat expansion at the tip while maintaining tighter tolerances where the primary cutting blades pass



Cracker Jaws

Offset teeth rows maximize the ability to downsize material

Cracker Jaws

Demolition

- Concrete Recycling

- C&D Processing

Patented pivot geometry creates peak power when jaws are near wide open, where it's most needed to crush concrete

Metric Specs:

Jaws	Weight*	Jaw Opening	Jaw Depth	Reach**	Minimum Excavator Weight	
	(kg)	(mm)	(mm)	(mm)	Boom Mount (mt)	Stick Mount (mt)
Shear	1,451	406	381	2,261	- 8	13
Cracker	1,451	635	635	2,515		

*Weight includes mounting bracket to attach to excavator. **Distance is measured from the attachment mounting pivot (boom or stick) forward. The stability of each lift class varies between OEM excavator models. Please consult with your Genesis salesperson for recommended carrier models. Every Genesis Versi Pro 15 is covered by a 12-month, 1,500-hour (whichever occurs first) warranty. Patents: genesisattachments.com/products/patents



1000 Genesis Drive, Superior, WI 54880 888-SHEAR-IT (743-2748) - Tel: 715.395.5252 - genesisattachments.com

