

Cyclone Grinder (GCG)



**IMPACT
TOOLS
GROUP**

FEATURES

- Two-hose system for easy installation, no case drain line required
- Soft start system and protective valving protect hydraulic motor
- Cutting drums are mounted to an optimized square drive shaft for easy maintenance and security
- Heavy-duty bearings and seals withstand harsh applications
- Optimized pick pattern for smooth and powerful operation

APPLICATIONS

- Demolition
- Concrete Grinding
- Tunneling/Mining
- Excavation & Trenching
- Scaling
- Road & Bridge
- Utility

| Model | Weight (lbs.) | Drive Type | Input Power (hp) | Output Shaft Torque (ft-lb at 5075 psi) | Drum Diameter (ins.) | Drum Width (ins.) | Number of Picks | Maximum Oil Flow (gpm) | Optimum Oil Flow (gpm) | Maximum Pressure (psi) | Working Pressure Range (psi) | Excavator Weight (lbs.) |
|----------------|------------------|------------|---------------------|--|-------------------------|----------------------|-----------------|---------------------------|---------------------------|---------------------------|---------------------------------|----------------------------|
| GCG 2 | 145 | Chain | 13 | 805* | 11 | 12 | 46 | 15 | 8 | 3,260 | 725 - 3,260 | 1,400 - 5,000 |
| GCG 5 | 400 | Gear | 29 | 3,257 | 13 | 16 | 32 | 17 | 11 | 5,800 | 2,600 - 5,800 | 5,000 - 12,000 |
| GCG 8 | 442 | Gear | 59 | 3,454 | 13 | 16 | 32 | 26 | 22 | 5,800 | 2,600 - 5,800 | 10,000 - 20,000 |
| GCG 10 | 938 | Direct | 39 | 3,078 | 17 | 29 | 56 | 30 | 16 | 5,800 | 2,600 - 5,800 | 16,000 - 24,000 |
| GCG 15 | 1,311 | Direct | 55 | 9,445 | 19 | 33 | 64 | 35 | 32 | 5,800 | 2,600 - 5,800 | 24,000 - 36,000 |
| GCG 20 | 2,577 | Direct | 94 | 11,506 | 25 | 42 | 64 | 85 | 58 | 5,800 | 2,600 - 5,800 | 36,000 - 50,000 |
| GCG 30 | 3,188 | Direct | 147 | 17,178 | 27 | 46 | 60 | 120 | 85 | 5,800 | 2,600 - 5,800 | 52,000 - 76,000 |
| GCG 40 | 3,664 | Gear | 188 | 29,742 | 27 | 33 | 54 | 140 | 95 | 5,800 | 2,600 - 5,800 | 60,000 - 100,000 |
| GCG 50 | 5,420 | Gear | 188 | 27,898 | 29 | 41 | 56 | 140 | 95 | 5,800 | 2,600 - 5,800 | 84,000 - 100,000 |
| GCG 60 | 5,463 | Gear | 295 | 34,658 | 29 | 41 | 56 | 180 | 142 | 5,800 | 2,600 - 5,800 | 100,000 - 130,000 |
| GCG 125 | 11,965 | Gear | 536 | 100,852 | 36 | 59 | 76 | 265 | 210 | 5,800 | 2,600 - 5,800 | 130,000 - 250,000 |

* at 3263 psi

The GCG is covered by a 12-month, 1,500-hour (whichever occurs first) warranty.

Genesis reserves the right to continually make product improvements designed to positively enhance performance.

Patents: genesisattachments.com/products/patents



1000 Genesis Drive, Superior, WI 54880

888-SHEAR-IT (743-2748) – Tel: 715.395.5252 – genesisattachments.com