

Cyclone Grinder (GCG)



**IMPACT
TOOLS
GROUP**

FEATURES

- Two-hose system for easy installation, no case drain line required
- Soft start system and protective valving protect hydraulic motor
- Cutting drums are mounted to an optimized square drive shaft for easy maintenance and security
- Heavy-duty bearings and seals withstand harsh applications
- Optimized pick pattern for smooth and powerful operation

APPLICATIONS

- Demolition
- Concrete Grinding
- Tunneling/Mining
- Excavation & Trenching
- Scaling
- Road & Bridge
- Utility

Model	Weight (lbs.)	Drive Type	Input Power (hp)	Output Shaft Torque (ft-lb at 5075 psi)	Drum Diameter (ins.)	Drum Width (ins.)	Number of Picks	Maximum Oil Flow (gpm)	Optimum Oil Flow (gpm)	Maximum Pressure (psi)	Working Pressure Range (psi)	Excavator Weight (lbs.)
GCG 2	145	Chain	13	805*	11	12	46	15	8	3,260	725 - 3,260	1,400 - 5,000
GCG 5	400	Gear	29	3,257	13	16	32	17	11	5,800	2,600 - 5,800	5,000 - 12,000
GCG 8	442	Gear	59	3,454	13	16	32	26	22	5,800	2,600 - 5,800	10,000 - 20,000
GCG 10	938	Direct	39	3,078	17	29	56	30	16	5,800	2,600 - 5,800	16,000 - 24,000
GCG 15	1,311	Direct	55	9,445	19	33	64	35	32	5,800	2,600 - 5,800	24,000 - 36,000
GCG 20	2,577	Direct	94	11,506	25	42	64	85	58	5,800	2,600 - 5,800	36,000 - 50,000
GCG 30	3,188	Direct	147	17,178	27	46	60	120	85	5,800	2,600 - 5,800	52,000 - 76,000
GCG 40	3,664	Gear	188	29,742	27	33	54	140	95	5,800	2,600 - 5,800	60,000 - 100,000
GCG 50	5,420	Gear	188	27,898	29	41	56	140	95	5,800	2,600 - 5,800	84,000 - 100,000
GCG 60	5,463	Gear	295	34,658	29	41	56	180	142	5,800	2,600 - 5,800	100,000 - 130,000
GCG 125	11,965	Gear	536	100,852	36	59	76	265	210	5,800	2,600 - 5,800	130,000 - 250,000

* at 3263 psi

Genesis reserves the right to continually make product improvements designed to positively enhance performance.

Patents: genesisattachments.com/products/patents