

Cyclone Grinder (GCG)



**IMPACT
TOOLS
GROUP**

FEATURES

- Two-hose system for easy installation, no case drain line required
- Soft start system and protective valving protect hydraulic motor
- Cutting drums are mounted to an optimized square drive shaft for easy maintenance and security
- Heavy-duty bearings and seals withstand harsh applications
- Optimized pick pattern for smooth and powerful operation

APPLICATIONS

- Demolition
- Concrete Grinding
- Tunneling/Mining
- Excavation & Trenching
- Scaling
- Road & Bridge
- Utility

Metric Specs:

Model	Weight	Drive Type	Input Power	Output Shaft Torque	Drum Diameter	Drum Width	Number of Picks	Maximum Oil Flow	Optimum Oil Flow	Maximum Pressure	Working Pressure Range	Excavator Weight
	(kg)		(kW)	(Nm at 350 bar)	(mm)	(mm)		(lpm)	(lpm)	(bar)	(bar)	(mt)
GCG 2	66	Chain	10	1,091*	279	305	46	57	30	225	50 - 225	0.6 - 2.3
GCG 5	181	Gear	22	4,416	330	406	32	64	42	400	179 - 400	2.3 - 5.4
GCG 8	200	Gear	44	4,683	330	406	32	98	83	400	179 - 400	4.5 - 9
GCG 10	425	Direct	29	4,173	432	737	56	114	61	400	179 - 400	7 - 11
GCG 15	595	Direct	41	12,806	483	838	64	132	121	400	179 - 400	11 - 16
GCG 20	1,169	Direct	70	15,600	635	1,067	64	322	220	400	179 - 400	16 - 23
GCG 30	1,446	Direct	110	23,290	686	1,168	60	454	322	400	179 - 400	24 - 34
GCG 40	1,662	Gear	140	40,325	686	838	54	530	360	400	179 - 400	27 - 45
GCG 50	2,458	Gear	140	37,825	737	1,041	56	530	360	400	179 - 400	38 - 45
GCG 60	2,478	Gear	220	46,990	737	1,041	56	681	538	400	179 - 400	45 - 59
GCG 125	5,427	Gear	400	136,737	914	1,499	76	1,003	795	400	179 - 400	59 - 113

* at 225 bar

Genesis reserves the right to continually make product improvements designed to positively enhance performance.

Patents: genesisattachments.com/products/patents