

Concrete Processor (GCP)

FEATURES

- 1 Power is derived from a protected large-bore cylinder, eliminating the need for an intensifier
- 2 One-piece bolt-on tooth bed and bottom wear pad protect parent material, are quick and easy to replace, and minimize build-up and hard-surfacing
- 3 Bolt-on rebar cutting blades and weld-in blade pockets are easy to replace and reduce maintenance
- 4 Large jaw opening readily pulverizes thick concrete
- 5 Heavy-duty pivot design with recessed end caps provides structural strength and long-term durability
- 6 Proprietary regeneration valve improves cycle time by up to 33% compared to standard hydraulic systems
- 7 Built with Strenx™ steel for the best combination of structural strength and wear durability

APPLICATIONS

- Concrete Recycling
- Demolition



Model	Weight*	Jaw Opening	Jaw Depth	Jaw Width	Reach**	Minimum Excavator Wt.
	(lbs.)	(ins.)	(ins.)	(ins.)	(ft. ins.)	Stick Mount (lbs.)
GCP 410	4,650	34	29	20	6' 9"	45,000
GCP 410R	6,650	34	29	20	7' 9"	55,000
GCP 610	7,950	45	39	24	8' 8"	65,000
GCP 610R	9,950	45	39	24	9' 8"	85,000

*Weight includes mounting bracket to attach to excavator.

**Distance is measured from the attachment mounting pivot (boom or stick) forward.

Genesis Concrete Processors are covered by a 12-month, 1,500-hour (whichever occurs first) warranty.

Genesis reserves the right to continually make product improvements designed to positively enhance performance.

Strenx™ is a trademark of SSAB.

Patents: genesisattachments.com/patents