

# Rail Breaker (GRB)



## FEATURES

- 1 Four-blade design reduces jaw wear and maintenance
- 2 Large-bore cylinder produces more power for improved cutting
- 3 Heavy-duty pivot group with flush caps for increased durability
- 4 Deep jaw design for cutting in the center of the blades
- 5 Streamlined hydraulic system reduces maintenance
- 6 Advanced technology protects rotational components from hydraulic pressure spikes

**JAW ARMOR**  
COMPATIBLE

## APPLICATION

- Rail Processing:  
**136 lb. and smaller low chrome**

Model	Weight*	Jaw Opening	Jaw Depth	Reach**	Minimum Excavator Wt.	
	(lbs.)	(ins.)	(ins.)		Boom Mount (lbs.)	Stick Mount (lbs.)
<b>GRB 30</b>	6,900	9.75	13.25	9' 2"	40,000	55,000

\*Weight includes mounting bracket to attach to excavator.

\*\*Distance is measured from the attachment mounting pivot (boom or stick) forward.

The GRB is covered by a 12-month, 1,500-hour (whichever occurs first) warranty.

Genesis reserves the right to continually make product improvements designed to positively enhance performance.

Patents: [genesisattachments.com/products/patents](http://genesisattachments.com/products/patents)