Severe-Duty Grapple



(GSD)



## FEATURES

- Replaceable tine tips are abrasion-resistant Hardox® steel
- 2 Boxed-tine construction creates a very high strength and lightweight grapple – each tine will withstand the full breakout force of the excavator
- Recessed welds are protected from wear, increasing grapple life
- Patented pivot group features a large pivot shaft, and bearings provide long-term durability
- Stiff arm and mounting pad included

## **APPLICATIONS**

- Demolition
- Scrap Handling & Compaction
- Rip-Rap Handling
- Road Building & Reconstruction
- C&D Sorting
- Land Clearing



## **Metric Specs:**

Model	Weight*	Capacity	Jaw Opening**	Jaw Closed	Moveable Jaw Width	Lower Jaw Width	Excavator Weight
	(kg)	(m³)	(mm)	(mm)	(mm)	(mm)	(mt)
GSD 10	252	0.4 - 0.6	1,626	178	330	559	5 - 9
GSD 30	957	1.1 - 1.9	2,134	203	533	889	11 - 14
GSD 40	1,188	1.5 - 2.3	2,337	229	660	965	14 - 18
GSD 50	1,497	2.3 - 3.1	2,515	254	762	1,118	16 - 29
GSD 70	2,009	2.7 - 3.4	3,073	305	762	1,118	29 - 39
GSD 90	2,699	3.4 - 5.0	3,327	305	864	1,270	39 - 54
GSD 140	3,402	5.0 - 5.7	3,556	381	864	1,270	54 - 77
GSD 170	4,354	5.7 - 7.6	3,810	406	1,016	1,473	77 - 100
GSD 250	7,484	6.5 - 9.2	3,810	406	1,016	1,727	100 - 127

Genesis Severe-Duty Grapples are covered by a 12-month, 1,500-hour (whichever occurs first) warranty. Genesis reserves the right to continually make product improvements designed to positively enhance performance.

Patents: genesisattachments.com/products/patents Hardox® is a trademark of the SSAB group of companies.



1000 Genesis Drive, Superior, WI 54880 888-SHEAR-IT (743-2748) - Tel: 715.395.5252 - genesisattachments.com



<sup>\*</sup>Weight includes mounting bracket and stiff arm.

\*\*Jaw opening varies slightly depending on excavator mounting location.