

# XT Mobile Shear (GXT)



## FEATURES

- 1 All the power in a shorter, lighter shear with a center of gravity closer to the excavator. Most models mount on smaller size carriers for lower initial investment and hourly operating costs.
- 2 Bolt-on piercing tip encapsulates front of upper jaw, minimizing risk of damage while reducing welding build-up and downtime
- 3 Short primary cutting blades position apex closer to the rear of the jaws and draw material further into the jaws where higher force makes efficient cuts
- 4 Weld-on, replaceable, highly abrasion-resistant steel rhino horn protects front of upper jaw, reducing downtime and welding build-up
- 5 Dual guide blade length matches piercing tip length enabling blades to be shimmed independently to accommodate piercing tip wear
- 6 Improved jaw geometry makes it easier to pick up material and reduces wear from ground contact
- 7 Reverse-mounted hydraulic cylinder shortens shear length and weight while protecting rod from damage
- 8 Remote-mounted hydraulic speed valve improves serviceability and minimizes stress on other critical hydraulic components
- 9 Lower shear height improves visibility while providing superior rigidity and structural integrity

### APPLICATIONS

- Scrap Processing
- Demolition

**SHEAR**  
**JAW ARMOR**  
COMPATIBLE

**Pulse**  
TECHNOLOGY  
COMPATIBLE

Model	Weight*	Jaw Opening	Jaw Depth	Reach**	Min. Excavator Wt.	
	(lbs.)	(ins.)	(ins.)	(ft. ins.)	Boom Mount*** (lbs.)	Stick Mount*** (lbs.)
<b>GXT 115****</b>	3,100	16	18	5' 0"	15,000	25,000
<b>GXT 115R****</b>	3,550	16	18	7' 8"	18,000	30,000
<b>GXT 225</b>	4,200	18	20	5' 8"	25,000	35,000
<b>GXT 225R</b>	4,900	18	20	7' 11"	30,000	45,000
<b>GXT 335</b>	6,500	23	26	6' 5"	27,000	45,000
<b>GXT 335R</b>	7,300	23	26	8' 11"	37,000	66,000
<b>GXT 445</b>	9,500	28	28	7' 2"	40,000	75,000
<b>GXT 445R</b>	11,000	28	28	10' 1"	48,000	90,000
<b>GXT 555</b>	11,600	30	30	8' 0"	50,000	90,000
<b>GXT 555R</b>	13,100	30	30	11' 0"	55,000	110,000
<b>GXT 665</b>	13,200	32	32	9' 0"	55,000	110,000
<b>GXT 665R</b>	14,700	32	32	12' 0"	68,000	120,000
<b>GXT 775</b>	15,500	35	37	9' 8"	68,000	135,000
<b>GXT 775R</b>	17,750	35	37	13' 0"	79,000	150,000
<b>GXT 995</b>	18,000	39	42	10' 8"	79,000	170,000
<b>GXT 995R</b>	20,000	39	42	14' 2"	100,000	180,000
<b>GXT 1555</b>	23,000	44	46	13' 5"	110,000	190,000
<b>GXT 1555R</b>	26,750	44	46	17' 2"	145,000	250,000
<b>GXT 2055</b>	32,000	48	50	14' 5"	145,000	Contact Factory
<b>GXT 2055R</b>	36,200	48	50	17' 7"	180,000	Contact Factory
<b>GXT 2555</b>	50,500	54	56	15' 5"	Contact Factory	Contact Factory
<b>GXT 2555R</b>	56,500	54	56	21' 5"	Contact Factory	Contact Factory

\*Weight includes mounting bracket to attach to excavator. \*\*Distance is measured from the attachment mounting pivot (boom or stick) forward.

\*\*\*\*2<sup>nd</sup>-member installations that are at or near minimum excavator weight and all 3<sup>rd</sup>-member installations require pre-approval from Genesis.

\*\*\*\*\*The GXT 115 and GXT 115R have a single guide blade. GXT shears are covered by a 12-month, 1,500-hour (whichever occurs first) warranty.

Genesis reserves the right to continually make product improvements designed to positively enhance performance.

Patents: genesisattachments.com/products/patents